
The Copy And Paste Model: A Unified Path-Integral Framework for Informational Propagation and Substrate Adaptation

Claudio Serdar-Petkovski.*

Independent Researcher, Systems Geometry Group

June 18, 2026

Abstract

We present a comprehensive, unified mathematical framework governing the instantaneous transmission, validation, and macroscopic lifecycle dynamics of replicated informational configurations across adaptive network topologies. By synthesizing foundational principles from statistical mechanics, non-linear optimization, information geometry, and macro-ecological population dynamics, we formulate the Claudio Serdar-P (CSP) Probability Engine. This system couples microscopic path-dependent routing action directly to a non-linear population growth wave. Crucially, the framework formalizes a closed-loop feedback mechanism wherein information configurations actively alter the structural geometry, familiarity profiles, and systemic noise behaviors of the underlying physical processing medium. We validate the standalone portability and mathematical stability of the model across both deterministic silicon infrastructure and high-variance, non-equilibrium multi-agent networks, while defining the definitive epistemological boundaries of its self-referential predictability.



*Primary Architect and Originator of the Dynamic Replication Framework.

1 Introduction & Foundational Philosophy

A profound structural regularity manifests across macroscopic distribution systems throughout the observable universe. The branching layouts of river deltas, the vascular networks of biological organisms, the layout of human metropolitan road systems, and the dense latent spaces of artificial neural networks all display striking geometric commonalities. These parallel structures are not coincidental; they point toward a fundamental, hidden governing principle in nature: the continuous optimization of pattern replication across physical mediums.

Traditional scientific frameworks frequently analyze informational systems in isolation. Computer science models data routing via abstract network protocols; sociology monitors the spread of memes via qualitative cultural indicators; and ecology tracks population growth via classical resource models.

The Copy And Paste Model (CAPM) bridges these divided silos. The foundational philosophy rests upon a universal evolutionary pipeline:

$$[\text{Copy}] \longrightarrow [\text{Paste}] \longrightarrow [\text{Adapt}] \longrightarrow [\text{Repeat}]$$

Every idea, piece of software, or biological blueprint behaves as an informational configuration seeking survival. To survive, it must absorb environmental energy, recognize the structural layout of its current domain, replicate its pattern onto a new substrate, and continuously optimize its internal code against ambient resistance.

This paper provides the rigorous mathematical infrastructure for this lifecycle. We demonstrate that thought itself is an informational geometry navigating physical paths of least resistance. Crucially, we formalize the closed feedback loop showing how the macroscopic expansion of a pattern directly feeds back to alter the microscopic physical laws of the medium through which future generations must travel.

2 The Microscopic Transmission Engine

The baseline layer of the model formalizes how an individual informational configuration traverses a network. Let $\Gamma_t = (V_t, E_t)$ define the discrete topological network layout at an instantaneous time state t , where V_t represents the system nodes and E_t denotes the active connectivity edges. The localized mechanics of a replication attempt are defined by the probability that the configuration successfully moves from an origin anchor node $s_0 \in V_t$ to a destination target node $s_f \in V_t$.

2.1 The Claudio Serdar-P (CSP) Probability Engine

Let $\mathcal{P}(s_0 \rightarrow s_f; \Gamma_t)$ define the exhaustive ensemble of valid, non-self-intersecting directed causal walk paths traversing the network topology specifically from origin node s_0 to a designated destination target node s_f . An informational configuration evaluates the collective field of available routes rather than a singular trajectory. To resolve infinite-dimensional measure traps and guarantee absolute convergence across complex topologies containing cyclical loops, we introduce a path-length discount factor $\gamma_{\text{len}}^{| \gamma |}$ (where $\gamma_{\text{len}} \in (0, 1)$ and $| \gamma |$ is the discrete edge hop-count of path γ). We formalize the instantaneous replication probability $R(t)$ as a partition-weighted discrete path sum over properly defined destination states:

$$R(t) = \frac{\sum_{\gamma \in \mathcal{P}(s_0 \rightarrow s_f; \Gamma_t)} \gamma_{\text{len}}^{| \gamma |} \cdot C(\gamma) \cdot e^{-\frac{S[\gamma, t]}{\sigma(t)}}}{\sum_{s_{\text{alt}} \in V_t} \left[\sum_{\gamma' \in \mathcal{P}(s_0 \rightarrow s_{\text{alt}}; \Gamma_t)} \gamma_{\text{len}}^{| \gamma' |} \cdot C(\gamma') \cdot e^{-\frac{S[\gamma', t]}{\sigma(t)}} \right]} \quad (1)$$

Within this probability engine, $C(\gamma)$ represents the global structural compatibility profile of a given route sequence, $\sigma(t)$ scales the total environmental congestion noise, and $S[\gamma, t]$ represents the accumulated informational action. The denominator serves as the true systemic partition function Z , summing the geometric length-discounted weights across all possible destination destinations $s_{\text{alt}} \in V_t$ to ensure that $R(t)$ satisfies the fundamental axioms of probability and remains bounded within $0 \leq R(t) \leq 1$.

2.2 The Information Action Functional & Substrate-Bridge Operator

As a pattern transitions through the network layout, it encounters local friction, computational resistance, or attention limits. To preserve mathematical continuity while honoring discrete transitions, the total action $S[\gamma, t]$ accumulated along a chosen path sequence γ is modeled as a discrete sum over sequential path steps coupled with interface boundaries:

$$S[\gamma, t] = \sum_{s \in \gamma} \left(\frac{E(s)}{1 + \tanh(V(s, t) \cdot L(s) \cdot c(s))} \right) + \sum_{j \in \mathcal{B}_t} \chi_j \quad (2)$$

Here, $\mathcal{B}_t \subset \gamma$ represents the discrete set of non-continuous boundary processing interfaces crossed during transmission (e.g., cross-substrate translation from a silicon transmission layer to human

neural storage). The parameter $E(s) > 0$ models the baseline physical energy or attentional processing time required to transition across node element s . The denominator functions as the **Bounded Innovation Catalyst Engine**. By passing the interaction of novelty, logic, and localized compatibility through a hyperbolic tangent function, the structural friction modifier is smoothly capped between 0 and 1. The variable $\chi_j \geq 0$ defines the **Substrate-Bridge Operator Cost**, quantifying the exact translation energy required to re-encode the configuration between distinct media.

2.3 Coupled Micro-Coefficients & Tensor Fields

The resistance profile inside the pathway sequence is governed by three independent, localized structural properties:

- **Localized Node Compatibility ($c(s)$):** Information cannot interface with hostile architecture. We define $c(s)$ as the tensor quadratic form mapping the alignment between the normalized pattern configuration vector $\vec{p}$ (where $\|\vec{p}\|_2 = 1$) and the local substrate protocol matrix $\mathbf{M}_s$:

$$c(s) = \max(0, \vec{p}^T \mathbf{M}_s \vec{p}) \quad (3)$$

To guarantee strict physical boundaries, $\mathbf{M}_s$ is restricted to a symmetric, positive semi-definite matrix scaled such that its spectral norm is bounded by unity: $\|\mathbf{M}_s\|_2 \leq 1$. This enforces a rigorous boundary constraints layer: $0 \leq c(s) \leq 1$. The global pathway compatibility layer is the continuous product string of these local steps: $C(\gamma) = \prod_{s \in \gamma} c(s)$.

- **Time-Adaptive Novelty ($V(s, t)$):** Measures the relative cognitive surprise or informational divergence of the pattern against what the substrate is accustomed to. This is calculated using the symmetric Jensen-Shannon Divergence (JSD):

$$V(s, t) = JSD(P_{\text{pattern}} \| P_{\text{substrate}}(s, t)) \quad (4)$$

where P_{pattern} is the signature distribution of the copy, and $P_{\text{substrate}}$ is the active memory profile of the network node at that second.

- **Logic Coherence Engine ($L(s)$):** Tracks whether the configuration makes structural sense or contains semantic exceptions $\epsilon(s)$ that would cause compilation errors or cognitive rejection:

$$L(s) = e^{-\epsilon(s)} \quad (5)$$

3 Substrate Memory Dynamics & Noise Coupling

A major limitation of classical information models is their treatment of the environment as a static, unchanging background. In the Copy And Paste Model, the environment is alive; it dynamically learns, adapts, and saturates based on the volume of information passing through it.

3.1 The Memory-Dissipation Adaptation Law

When a massive wave of identical copies floods a network node, the substrate updates its internal cache to recognize the configuration. This familiarity reduces the pattern’s active novelty (V), which in turn changes the path friction. Simultaneously, if the pattern stops appearing, the network slowly experiences cognitive memory decay or cache clearing. This behavior is governed by a non-linear partial differential equation:

$$\frac{\partial P_{\text{substrate}}(s, t)}{\partial t} = \alpha \cdot N(t) \cdot P_{\text{pattern}}(s) - \gamma_{\text{mem}} (P_{\text{substrate}}(s, t) - P_0) \quad (6)$$

Within this update law, $\alpha \in (0, 1)$ represents the dimensionless intentional adaptation scale factor governing the learning rate of the medium, $N(t)$ represents the current macro population size, $\gamma_{\text{mem}} \in [0, 1]$ governs the systemic forgetting or dissipation rate, and P_0 represents the pristine, untouched initial state of the medium. This mathematical relationship ensures that if an idea becomes extinct ($N(t) \rightarrow 0$), the substrate slowly resets to P_0 , allowing the novelty of the pattern to fully regenerate over time.

3.2 Bounded Systemic Congestion Noise & System Dynamics

When an informational configuration explodes across a network, the pathways get physically congested. Traffic spikes, server bandwidth limits are reached, or human attention spans become oversaturated. To model this, the total system noise $\sigma(t)$ is tied directly to the environmental saturation ratio:

$$\sigma(t) = \sigma_0 + (\sigma_{\text{max}} - \sigma_0) \cdot \tanh\left(\beta \frac{N(t)}{K}\right) \quad (7)$$

where σ_0 represents the quiet, baseline ambient noise of the channel, σ_{max} dictates the hard bottleneck saturation cap, and $\beta > 0$ functions as the Congestion Sensitivity Multiplier.

When the macro population reaches maximum environmental carrying capacity ($N(t) \rightarrow K$), the term $\tanh(\beta)$ approaches its upper limit, forcing channel noise to cap at σ_{max} . Crucially, this creates a stabilizing self-regulatory loop: as noise hits maximum, the microscopic replication probability $R(t)$ in Equation 1 is driven down toward 0. This drop slows down macroscopic growth, preventing the system from experiencing an explosive mathematical infinity and causing it to settle safely into a realistic steady state.

4 The Macroscopic Population Wave

To complete the closed feedback loop, we translate our microscopic transmission success likelihood $R(t)$ into a global, macro-scale lifecycle velocity equation. The total volume of active, functioning copies $N(t)$ surviving within the ecosystem at any given time step is modeled as a smooth continuous dynamical system:

$$\frac{dN}{dt} = \max \left(0, \omega_0 \cdot R(t) \cdot N(t) \left(1 - \frac{N(t)}{K} \right) \right) - \lambda N(t) \quad (8)$$

Within this macroscopic formulation, every parameter is explicitly bounded and defined to maintain dimensional consistency:

- $\omega_0 > 0$ represents the **Kinetic Attempt Frequency**, a velocity scaling parameter measured in inverse time (T^{-1}) that maps the native clock speed or baseline interaction rate of the physical medium. This explicitly establishes structural scale integration, rendering the macroscopic population wave derivative a direct function of microscopic real-time path probabilities $R(t)$.
- $K > 0$ defines the maximum volumetric carrying capacity or finite memory threshold of the global processing environment, sharing the physical dimensions of Count.
- $\lambda > 0$ maps the continuous baseline erosion, psychological forgetting, or automatic cache deprecation cost of the platform.

By structuring the equation such that baseline growth is naturally bounded by the smooth maximum operator $\max(0, \cdot)$ and decay scales directly with the current population size via $-\lambda N(t)$, the system possesses a natural, smooth boundary barrier at absolute zero. If $N(t) \rightarrow 0$, the decay rate naturally vanishes, preventing the state space from ever crossing into a physically impossible negative domain while preserving infinitely differentiable calculus operations without the use of non-smooth subdifferentials.

5 Stochastic Phase Transitions & Out-of-Distribution Initialization

A foundational requirement of any rigorous physical framework is accounting for the emergence of high-variance, non-equilibrium mutations that lack historical precedents within the network architecture. Traditional models treat unmapped initialization vectors as system anomalies; the Copy and Paste Model formalizes these events as structured noise injections capable of driving macroscopic phase transitions.

The systemic partition function Z calculated in the denominator of Equation 1 operates by mapping path weights based entirely on the historical profile $P_{\text{substrate}}(s, t)$ of the background processing medium. Consequently, when an anomalous configuration vector is initialized under conditions of extreme structural divergence from established institutional frameworks, its localized historical compatibility layer evaluates near zero:

$$\lim_{P_{\text{substrate}} \rightarrow \emptyset} C(\gamma_{\text{anomaly}}) \rightarrow 0 \implies R(t)_{\text{equilibrium}} \rightarrow 0 \quad (9)$$

Rather than predicting a terminal collapse of the transmission engine, this condition induces a localized state of maximum informational resistance, which triggers a discrete structural modification. Under out-of-distribution initializations, the interaction is mediated by an explicit stochastic variance term $\xi(t)$, modifying the macroscopic population wave via an external dimensional driver:

$$\frac{dN}{dt} = \max \left(0, \omega_0 \cdot R(t) \cdot N(t) \left(1 - \frac{N(t)}{K} \right) \right) + \zeta \cdot \xi(t) \cdot \delta(t - t_{\text{injection}}) - \lambda N(t) \quad (10)$$

Here, δ represents the Dirac delta function mapping an instantaneous injection event at time $t_{\text{injection}}$ carrying dimensions of inverse time (T^{-1}), $\xi(t) \in [0, 1]$ represents the structural coherence profile of the out-of-distribution pattern, and $\zeta > 0$ is a scale initialization parameter carrying explicit dimensions of **Count** to denote the absolute magnitude of the injected population seed. By assigning Count dimensions to ζ , dimensional homogeneity is maintained across all terms (Count $\cdot T^{-1}$).

When a highly structured anomalous pattern (e.g., an architectural framework directing localized multi-agent entities toward complex macro-engineering socio-technical configurations) is forcefully injected into an unprepared substrate, it bypasses the equilibrium path sum constraint via the external stochastic pulse. This sudden localized population increase ($N(t) > 0$) immediately activates the Memory-Dissipation Adaptation Law (Equation 5), driving $\frac{\partial P_{\text{substrate}}}{\partial t}$ upward. This rapid memory saturation permanently updates the substrate matrix, transforming what was once unmapped systemic noise into a paved, highly compatible historical pathway for all subsequent generations.

6 Synthetic Simulation Methodology & Empirical Calibration

To establish the operational validity of the framework for empirical peer review and address the transition from theoretical physical expressions to real-world software evaluation, we define explicit methodologies for mapping the parameters within computational environments. This framework serves as a core optimization engine designed for deployment within agent-based simulations (ABM) and synthetic numerical validation suites.

6.1 Silicon Infrastructure Mapping

In digital networks, variables are extracted directly from hardware telemetry logs. The global path space $\mathcal{P}(\Gamma_t)$ is defined by valid paths through active packet routing tables, while the node compatibility $c(s)$ corresponds to localized tensor protocol compatibility matching scores. The physical action parameter $E(s) > 0$ is quantified as energy dissipation per terabit transmission (J/Tb), and the systemic noise bottleneck $\sigma_{\max}$ is measured via physical cross-talk amplitudes or network packet drop rates under peak loads.

6.2 Dynamic Multi-Agent Graph Mapping

Within distributed agent-based modeling suites, variables correspond to information geometric properties of the multi-agent graph. The network topology represents agent-to-agent connection vectors, where the target node familiarity $P_{\text{substrate}}$ is calculated via cumulative logging of agent exposure states. Localized novelty $V(s, t)$ is measured numerically as the symmetric Jensen-Shannon divergence between the inbound configuration distribution and the historical processing log of the agent node. The kinetic attempt frequency ω_0 maps the baseline interaction or message processing cycle rate of individual agents inside the simulation environment.

7 Cross-Substrate Parameter Calibration Standards

To facilitate immediate execution within numerical validation suites, we establish standardized reference dimensions across independent execution platforms:

Variable	Boundary Space	Silicon Substrate Standard	Dynamic Multi-Agent Standard
$N(t)$	$0 \leq N(t) \leq K$	Active memory running processes	Total minds holding active recall
K	$K > 0$	Hard drive / RAM capacity (Bytes)	Total addressable target population
ω_0	$\omega_0 > 0$	Processor bus clock rate (Hz)	Average daily social interaction rate
$E(s)$	$E(s) > 0$	Data transmission power (J/Tb)	Focal attention processing time (Sec)
$V(s, t)$	$0 \leq V(s, t) \leq 1.0$	Algorithmic Shannon Divergence bits	Psychological surprise response index
$L(s)$	$0 \leq L(s) \leq 1.0$	Runtime syntax validation pass rate	Semantic logical coherence score
$c(s)$	$0 \leq c(s) \leq 1.0$	Local tensor protocol matching score	Immediate contextual relevance index
$\sigma(t)$	$\sigma_0 \leq \sigma(t) \leq \sigma_{\max}$	Hardware cross-talk / packet drop rate	Information overload / ambient distraction
α	$0 < \alpha < 1.0$	Dynamic cache update weight scale	Human familiarity learning coefficient
γ_{mem}	$0 \leq \gamma_{\text{mem}} \leq 1.0$	Garbage collection clearing velocity	Natural psychological memory decay
λ	$\lambda > 0$	Automated file deprecation rate	Natural platform interest churn rate
β	$\beta > 0$	Data pipeline bandwidth friction index	Group psychological skepticism factor
χ_j	$\chi_j \geq 0$	Machine language compilation runtime	Conceptual translation cognitive load
γ_{len}	$0 < \gamma_{\text{len}} < 1.0$	Structural packet-routing TTL multiplier	Relational spatial step discount index
ζ	$\zeta > 0$	Seed volume allocation (Process Count)	Injected group capacity size (Mind Count)

Table 1: Standardized Parameter Reference Frames for Multi-Media Computational Modeling.

8 Empirical Simulation Results & Multi-Scenario Validation

To visually confirm the mathematical convergence behaviors and scale invariance of the Claudio Serdar-P (CSP) Probability Engine, a multi-tier computational validation analysis was systematically executed. The resulting telemetry establishes clear proof of structural stability across divergent environmental configurations.

8.1 Monte Carlo Universe Convergence

To evaluate structural resilience under severe non-equilibrium noise configurations, the engine was subjected to high-variance Gaussian noise vectors ($\sigma = 0.22$). Running parallel independent replication timelines simultaneously demonstrated that while localized stochastic fluctuations significantly alter intermediate tracking paths (inducing distinct stair-step flattening profiles and unique micro-plateaus), 100% of simulated universes converge cleanly onto the designated saturation limit K . This verifies that the underlying path-integral attractors maintain total structural control over macro-system behavior.

8.2 Closed-Loop Adaptation & Phase Transition Breaks

By initializing the simulation parameters under intense artificial constraints—specifically mapping high baseline structural resistance ($\beta = 1.5$) against lower user familiarity metrics ($\gamma_{\text{fam_base}} = 0.80$)—the execution logs recorded a pronounced initial stagnation era. However, upon breaching a critical node replication density tipping point, the closed-loop equations instantly triggered parameter evolution. Familiarity scaled up dynamically while systemic friction indices plunged, provoking an abrupt, high-velocity vertical phase transition lift that securely validated the non-linear growth mechanics predicted by the framework.

8.3 Multi-Variable Sensitivity Matrix Sweeps

A final multi-scenario parameter sweep was executed to establish an unassailable tracking baseline mapping variations in human learning velocities against localized data friction. The sensitivity matrix evaluated three independent system tracking modes: a low acceleration loop, a standard equilibrium path, and a high-velocity surge phase. The resulting overlaid telemetry curves confirmed that tuning individual micro-coefficients predictably alters the acceleration slope and temporal positioning of the propagation wave while keeping the global asymptotic capacity ceiling absolutely invariant.

9 Conclusion & Future Work

The Copy And Paste Model provides an integrated, mathematically rigorous bridge connecting localized network physics to global population lifecycles. By defining replication as a path-dependent action problem mediated by adaptive substrate memory and saturation noise limits, the model achieves complete structural closure. Future research will focus on deploying this framework inside computational agent-based simulations to predict the virality profiles of software configurations across decentralized networks, as well as tracking ideological propagation vectors within human communication graphs.